

KM-3040

A3 MONOCHROME MULTIFUNCTIONALS

▶ print ▶ copy ▶ fax

FUNCTIONALITY THAT
GROWS WITH YOUR BUSINESS.



 **KYOCERA**

KM-3040

A3 MONOCHROME MULTIFUNCTIONALS

The KM-3040 incorporate extremely durable components that guarantee efficient and reliable operation to meet the demanding requirements of busy office environments. The KM-3040 provide effective productivity and maximise uptime while ensuring a minimum impact on the environment.

GENERAL

Technology: Kyocera Laser, Mono component
Engine speed: Max. 30/15 pages per minute A4/A3
Resolution: 600 x 600 dpi (copy), 1,800 dpi level x 600 dpi (copy, photo mode), 1200 dpi quality (print)
Time to first copy: 4.7 seconds or less
Warm-up time: 15 seconds or less from power on
Monthly duty cycle: 100,000 copies
Power source: AC 220 - 240 V, 50/60 Hz
Power consumption: Printing: 560 W, Stand-by: 160 W, Power-Saving (ECOpower): 3.2 W
Noise (ISO 7779): Printing/Copying: 66.5 dB(A)
Stand-by: 47 dB(A), Power-Saving (ECOpower): Immeasurably low
Dimensions (W x D x H): Main unit: 570 x 640 x 767.2 mm
Weight: Main unit: Approx. 75 kg
Certifications: TÜV/GS, CE
This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: 2 x 500-sheet universal paper feeder, 60-120 g/m², A3-A5R, Folio
200-sheet multi-purpose tray, 45-200 g/m², A3-A6R, Folio, envelopes
Max. input capacity with options: 2,200 sheets
Duplex as standard supports A3-A5, 60-80 g/m²
Output capacity: 250 sheets face-down

COPY FUNCTIONS

Max. original size: A3
Continuous copying: 1-999
Memory capacity: Standard 64 MB (max. 192 MB)
Zoom range: 25-400% in 1% steps (with DP-670: 25-200%)
Preset magnification ratios: 5R / SE
Digital features: Interrupt output job, scan once print many, electronic sort, rotate sort, rotate copy, N-up copy, split copy, cover mode, page numbering, margin shift, border erase
Exposure mode: Auto, manual: 7 or 13 steps
Image adjustments: Text + photo, text, photo

PRINT FUNCTIONS (OPTIONAL)

Processor: PowerPC 750Cxr / 400 MHz
Memory: Standard 64 MB (max. 576 MB) + 40 GB HDD (HD-5)
Emulations: PCL6 Incl. PCL KPD L3 (PostScript 3 compatible) Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630, KC-GL, PDF direct print
Controller language: PRESCRIBE IIe
Fonts: 80 outline fonts (PCL6), 136 PostScript KPDL 3 fonts, 1 bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode (PDF-417)
Downloadable fonts: Kyocera, PCL + TrueType format, Type 1 + 3 format
Features: eMPS - for quick copy, proof and hold, private print, job storage and job management functionality

Interfaces

Standard Interface: USB 2.0 (Hi-Speed), Fast Ethernet
10-Base-T/100Base-TX, CF slot, KUIO-IV option interface slot
Multiple Interface connection (MIC): Allows simultaneous data transfer via up to three interfaces, with each interface having its own virtual printer.

FAX FUNCTIONS (OPTIONAL)

Compatibility: ITU-T Super G3
Modem speed: Max. 33.6 kbps
Transmission speed: 3 seconds or less (JBIG)
Scanning density: Normal: 8 dot/mm x 3.85 line/mm, Fine: 8 dot/mm x 7.7 line/mm, Superline: 8 dot/mm x 15.4 line/mm, Ultrafine: 16 dot/mm x 15.4 line/mm (with optional memory), halftone
Max. original size: A3
Compression method: JBIG, MMR, MR, MH
Memory: Standard 4 MB, max. 32 MB
Features: Rotate transmission, confidential, relay and bulletin board transmission

OPTIONS

Printing System (Y), Fax System (P)

Paper handling
DP-670 Document processor: 75 sheets, 45-160 g/m², A3-A5R, Folio (RADF)
PF-670 Paper feeder: 2 x 500 sheets, 60-120 g/m², A3, A4, A4R, A5R, B4, B5, 85R, Letter, Letter-R, Legal, Ledger, Folio, STMT
DF-670 Document finisher: Max. 500 sheets A4 or 250 sheets A3, Folio, 60-105 g/m², one position stapling max. 30 sheets A4 or 20 sheets A3
DF-730 Document finisher + AK-670*: Max. 1,000 sheets A4 or 500 sheets A3/B4, 64-128 g/m², A3-B5, one position stapling max. 30 sheets A4 or 20 sheets A3/B4, 64-128 g/m²
JS-670 Job separator: 100 sheets internal job separator, 45-160 g/m², A3-A5R

*Adapter-Kit AK-670 is required for the use of DF-730 document finisher.

Memory

Copy Memory
DIMM memory: SDRAM DIMM 100 pin (64, 128 MB), 1 slot empty
Printer Memory
DIMM memory: DDR-SDRAM DIMM 100 pin (64, 128, 256, 512 MB), 1 slot empty
CompactFlash® card: 1 slot (up to 4 GB) for forms, fonts, logos, macro storage
HD-5 Hard disk: 40 GB, storage of data, formats, fonts etc. + eMPS, booklet printing
Fax Memory
MM-13-32: Image memory (28 MB)

Optional Interface for print functions
IB-23 Network card: 10Base-T/100Base-TX

Others

Platen cover (D)

CONSUMABLES

TK-679 Toner-Kit: Microfine toner for 20,000 pages with 6% coverage



Select your options to suit your needs:



Product depicted includes optional extras

Your Kyocera Business Partner:



Website: www.philcopy.net

KYOCERA MITA (UK) Ltd, 8 Beacontree Plaza, Gillette Way, READING RG2 0BS
Tel: 0118 931 1500, Fax: 0118 931 1108, email: info@kyoceramita.co.uk,
www.kyoceramita.co.uk

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

