

KM-2560/KM-3060

A3 MULTIFUNCTIONALS

▶ print ▶ copy ▶ scan ▶ fax

TREATS EVERY PROJECT
AS A PRIORITY.



 KYOCERA

KM-2560/KM-3060

A3 MULTIFUNCTIONALS

The KM-2560 and KM-3060 incorporate extremely durable components that guarantee efficient and reliable operation to meet the demanding requirements of busy office environments. The KM-2560 and KM-3060 provide effective productivity and maximise uptime while ensuring a minimal impact on the environment.

GENERAL

Technology: Kyocera Laser, Mono component

Engine speed:

KM-2560: Max. 25/12.5 pages per minute A4/A3

KM-3060: Max. 30/15 pages per minute A4/A3

Resolution: 600 x 600 dpi (copy), 1.800 dpi level x 600 dpi

(copy, photo mode), 1200 dpi quality (print)

Time to first copy:

KM-2560/KM-3060: 4,7 seconds or less

Warm-up time: 29 seconds or less from power on

Monthly duty cycle: 100,000 copies

Power source: AC 220 - 240 V, 50/60 Hz

Power consumption: Printing: 560 W, Stand-by: 160 W,

Power-saving (ECOpower): 8,7 W

Noise (ISO 7779):

KM-2560: Printing/Copying: 64,7 dB(A)

KM-3060: Printing/Copying: 66,5 dB(A)

Stand-by: 47 dB(A), Power-Saving (ECOpower):

Immeasurably low

Dimensions (W x D x H): Main unit: 570 x 620 x 767,2 mm

Weight: Main unit: Approx. 75 kg

Certifications: TÜV/GS, CE, ISO 15408 (under evaluation)

This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0,11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: 2 x 500-sheet universal paper feeder,

60-120 g/m², A3-ASR, Folio

200-sheet multi-purpose tray, 45-200 g/m², A3-A6R, Folio,

envelopes

Max. input capacity with options: 2,200 sheets

Duplex as standard supports A3-A5, 60-80 g/m²

Output capacity: 250 sheets face-down

COPY FUNCTIONS

Max. original size: A3

Continuous copying: 1-999

Memory capacity: Standard 512 MB (max. 1 GB)

+ 80 GB HDD (system shared)

Zoom range: 25-400% in 1% steps (with DP-670: 25-200%)

Preset magnification ratios: 5R / 5E

Digital features: Interrupt output job, scan once print many, electronic sort, rotate sort, rotate copy, N-up copy, split copy, cover mode, page numbering, box image overlay, margin shift, border erase

Exposure mode: Auto, manual: 7 or 13 steps

Image adjustments: Text + photo, text, photo

PRINT FUNCTIONS

Processor: PowerPC 750Cxr / 400 MHz

Memory: Standard 512 MB (max. 1 GB) + 80 GB HDD

(system shared)

Emulations: PCL6 incl. PjL, KPDL 3 (PostScript 3 compatible)

Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630,

KC-GL, PDF direct print

Controller language: PRESCRIBE file

Fonts: 80 outline fonts (PCL6), 136 PostScript KPDL 3 fonts,

1 bitmap font, 45 types of one-dimensional barcodes plus

two-dimensional barcode (PDF-417)

Downloadable fonts: Kyocera, PCL + TrueType format,

Type 1 + 3 format

Features: eMPS - for quick copy, proof and hold, private

print, job storage and job management functionality

Interfaces

Standard interface: USB 2.0 (Hi-Speed), USB Host interface

dedicated for USB Flash Memory device, Fast Ethernet

10-Base-T/ 100Base-TX, CF slot

Multiple interface connection (MIC): Allows simultaneous

data transfer via up to four interfaces, with each interface

having its own virtual printer.

SCAN FUNCTIONS

Functionality: Scan-to-SMB/FTP, scan-to-email, scan-to-BOX,

network TWAIN, BOX TWAIN

Scan speed: 50 originals per minute in b/w (300 dpi/A4),

15 originals per minute in colour (300 dpi/A4)

30 originals per minute in b/w (600 dpi/A4),

15 originals per minute in colour (600 dpi/A4)

Scan resolution: 600, 400, 300, 200, 200 x 400, 200 x 100 dpi

(256 greyscales, 256 colour)*

Max. scan size: A3

Original recognition: Text, photo, text + photo, OCR

Interface: 10Base-T/100Base-TX

Network protocol: TCP/IP

File types: Mono: TIFF, PDF

Colour: JPEG, PDF, TIFF (JPEG)

Compression format: B/W: C4 (MMR), Colour: JPEG

Bundle software: KM-NET Viewer, TWAIN source, PaperPort SE

*Colour scanning at resolutions of 400 dpi and above requires additional memory.

FAX FUNCTIONS (OPTIONAL)

Compatibility: ITU-T Super G3

Modem speed: Max. 33,6 kbps

Transmission speed: 3 seconds or less (JBIG)

Scanning density: Normal: 8 dot/mm x 3,85 line/mm,

Fine: 8 dot/mm x 7,7 line/mm, Superline: 8 dot/mm x 15,4

line/mm, Ultrafine: 16 dot/mm x 15,4 line/mm, SUFine:

600 x 600 dpi

Max. original size: A3

Compression method: JBIG, MMR, MR, MH

Memory: Standard 120 MB (enable fax image back up)

Features: Internet fax, network fax, rotate transmission,

confidential, relay and bulletin board transmission delivery to

document box

OPTIONS

Fax System (M)

Paper handling

DP-670 Document processor: 75 sheets, 45-160 g/m²,

A3-ASR, Folio (RADF), colour scan

PF-670 Paper feeder: 2 x 500 sheets, 60-120 g/m², A3, A4, A4R,

ASR, B4, B5, B5R, Letter, Letter-R, Legal, Ledger, Folio, STMT

DF-670 Document finisher: Max. 500 sheets A4 or

250 sheets A3, Folio, 60-105 g/m², one position

stapling max. 30 sheets A4 or 20 sheets A3

DF-730 Document finisher + AK-670*: Max. 1,000 sheets A4

or 500 sheets A3/B4, 64-128 g/m², A3-B5, one position

stapling max. 30 sheets A4 or 20 sheets A3/B4, 64-128 g/m²

JS-670 Job separator: 100 sheets internal job separator,

45-160 g/m², A3-ASR

*Adapter-Kit AK-670 is required for the use of DF-730 docu-

ment finisher.

Memory

DIMM memory: 512 MB memory, DDR-SDRAM DIMM

(100 pin): 2 slots (1 slot empty), max. 1 GB

CompactFlash* card: 1 slot (up to 4 GB) for forms, fonts,

logos, macro storage

Others

Platen cover (D)

CONSUMABLES

TK-679 Toner-kit: Microfine toner for 20,000 pages with 6% coverage



Select your options to suit your needs:



Product depicted includes optional extras

Your Kyocera Business Partner:



KYOCERA MITA (UK) Ltd., 8 Beacontree Plaza, Gillette Way, READING RG2 0BS
Tel: 0118 931 1500, Fax: 0118 931 1108, email: info@kyoceramita.co.uk, www.kyoceramita.co.uk

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

