

Liesegang



trainer portable e
trainer portable 400

Portable solutions for the mobile user – ready for use within a few seconds:

Liesegang overhead projectors.

With Liesegang's fold up system the projector needs very little space and is easy to set up.



trainer portable e
trainer portable 400

trainer portable e trainer portable 400



- High-end lens
- Electronic lamp control for lower weight
- Quick lamp changer
- Extremely low work top due to design with reflection system, therefore no line-of-sight obstruction for the presenter
- Lift technology – easy setup and storage
- Elegant robust case

Liesegang trainer portable e 0636 315 0000U
 Lens f = 12.4 in. (315 mm), incl. case
Accessories for Liesegang trainer portable e
 100 A4 transparencies ZU0601 40 4010
 Dust cover ZU0615 74 0000
 Spare lamp 24V /250 Watt /Type 310 ZU0310 05 2200

Liesegang trainer portable 400 0656 315 00000
 Lens f = 12.4 in. (315 mm), incl. case
Accessories for Liesegang trainer portable 400
 100 A4 transparencies ZU0601 40 4010
 Dust cover ZU0615 74 0000
 Spare lamp 36V /400 Watt /Type 610 ZU0610 02 2040

Technical Data	trainer portable e	trainer portable 400
Desktop	–	–
Can be integrated	–	–
Foldable column	–	–
Portable hydraulic column	•	•
Focus control	•	•
Lamp/Power		
Low-voltage halogen lamp	250 Watt	400 Watt
Quick lamp changer	•	•
Lifetime of lamp	up to 50 hrs	up to 50 hrs
Brightness (ANSI lumens)	2500 lm	4300 lm
Power save function	•	•
Equipment		
Anti-glare foldable fresnel lens	–	–
Anti-glare removable fresnel lens	–	–
Condensor lens with cold-light mirror	•	•
Color fringe correction	–	–
Plug for additional units	–	–
Pen holder	•	•
Submersible clips for single transparencies	–	–
Scroll cassette	–	–
Scroll attachment	–	–
General specifications		
Dimensions (D x W x H)	15.9 x 12.2 x 23.0	15.9 x 12.2 x 23.0
- In use in in. (approx.)	405 x 310 x 585	405 x 310 x 585
- In use in mm (approx.)	15.9 x 12.2 x 4.1	15.9 x 12.2 x 4.1
- During transportation in in. (approx.)	405 x 310 x 105	405 x 310 x 105
- During transportation in mm (approx.)	13.0 / 5,9	13.2 / 6,0
Weight in lbs/kg (approx.)	•	•
GS German safety seal	230 V /50-60 Hz	230 V /50-60 Hz
Power		

*S = Surcharge

Ed. Liesegang oHG
 Specialists in the Manufacture
 of Projection and Presentation Equipment
 Volmerswerther Straße 21
 D-40221 Düsseldorf
 Germany
 Phone +49 211 3901-1
 Fax +49 211 3901-227
 info@liesegang.de
 www.liesegang.de

Your Liesegang partner: